



EO220

Topside Range

TOPSIDE ENVIRONMENTAL OIL

EO220 is an environmentally superior alternative to existing ISO 220 Hydraulic Oils.

EO220 is based on environmentally acceptable oils and carries an OCNS Class E (for UK discharge) and Yellow 1 environmental profile (for Norwegian Discharge).

EO220 exhibits excellent lubrication, corrosion protection, stability, microbiological protection, material compatibility and all round technical performance.

EO220 is also available in a high di-electric (insulation) grade with a KeV >55 (to BS EN 60156 IEC 156), making it suitable for use in many electrical insulation related applications.

EO220 is capable of operating in a wide range of offshore hydraulic equipment; however, please always consult us prior to use to establish compatibility with your system and to clarify performance attributes.

EO environmental oils are also available in a number of viscosity versions including EO08, EO12, EO18, EO32, EO46, EO68, EO100 and EO150.

PHYSICAL PROPERTIES

Appearance	Colourless/Yellow
Pour Point (°C)	< -25
Specific Gravity	0.998
Viscosity @ 20 °C	615
Viscosity @ 40 °C	220
Water Solubility	Insoluble
Oil Solubility	Miscible



Offshore Environmental Oils

Walter Leigh Way, Moss Industrial Estate
Leigh, Lancashire, WN7 3PT, UK

Telephone +44 (0) 8452 967751

Fax +44 (0) 8452 967752

Email tech@offshore-oils.com

Website www.offshore-oils.com